

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

Solar Flux® Type B

Version number: 4.0

SECTION 1: Identification

1.1 Product identifier

Trade name Solar Flux® Type B

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses Welding powder

1.3 Details of the supplier of the safety data sheet

Golden Empire Corporation / Solar Flux Telephone: +1 424 645 8845

Calabasas, CA 91372 e-mail: eaw.solarflux@gmail.com

United States

e-mail (competent person) sdb@csb-online.de

Please do not use this e-mail address to ask for the latest safety data sheet. For this purpose contact Golden Empire Corporation / Solar Flux.

1.4 Emergency telephone number

As above or nearest toxicological information center.

SECTION 2: Hazard(s) identification

2.1 Classification of the substance or mixture

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Classification				
Section	Hazard class	Category	Hazard class and category	Hazard statement
A.6	carcinogenicity	1A	Carc. 1A	H350
A.7	reproductive toxicity	1B	Repr. 1B	H360FD
A.9	specific target organ toxicity - repeated exposure	1+2	STOT RE 1+2	H372,H373

For full text of abbreviations: see SECTION 16

The most important adverse physicochemical, human health and environmental effects

Delayed or immediate effects can be expected after short or long-term exposure.

2.2 Label elements

Labelling acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Signal word danger

Solar Flux® Type B

Version number: 4.0

Pictograms

GHS08



Hazard statements

H350 May cause cancer.
H360FD May damage fertility. May damage the unborn child (if swallowed).
H372 Causes damage to organs through prolonged or repeated exposure.
H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P260 Do not breathe dust.
P264 Wash thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection/...
P281 Wear personal protective equipment/face protection.
P308+P313 If exposed or concerned: Get medical advice/attention.
P314 Get medical advice/attention if you feel unwell.
P405 Store locked up.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazardous ingredients for labelling

manganese dioxide
quartz
boric acid

2.3 Other hazards

Hazards not otherwise classified

Contact with acids liberates very toxic gas.

Results of PBT and vPvB assessment

Does not contain a PBT-/vPvB-substance at a concentration of $\geq 0.1\%$.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not relevant (mixture).

3.2 Mixtures

Solar Flux® Type B

Version number: 4.0

Description of the mixture

Hazardous ingredients						
Name of substance	Identifier	Wt%	Classification acc. to GHS	Pictograms	Notes	Specific Conc. Limits
wollastonite (calcium metasilicate)	CAS No 13983-17-0	25 - < 50	-	-	-	-
calcium fluoride	CAS No 7789-75-5	10 - < 20	cD / OSHA003	-	-	-
quartz	CAS No 14808-60-7	10 - < 20	Carc. 1A / H350 STOT RE 1 / H372		IARC: 1	-
manganese dioxide	CAS No 1313-13-9	5 - < 10	Acute Tox. 4 / H302 Acute Tox. 4 / H332 STOT RE 2 / H373 cD / OSHA003 EUH031	 	-	-
boric acid	CAS No 10043-35-3	3 - < 5	Repr. 1B / H360FD		11	-
manganese	CAS No 7439-96-5	1 - < 3	cD / OSHA003	-	-	-
lithium fluoride	CAS No 7789-24-4	1 - < 3	Acute Tox. 4 / H302 Eye Irrit. 2A / H319 cD / OSHA003 EUH032		-	-

Notes

11: The classification of mixtures as reproductive toxicant is necessary if the sum of the concentrations of individual boron compounds that are classified as reproductive toxicant in the mixture as placed on the market is $\geq 0,3\%$.
IARC: 1: IARC group 1: carcinogenic to humans (International Agency for Research on Cancer)

Remarks

For full text of H-phrases: see SECTION 16

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

SECTION 4: First-aid measures

4.1 Description of first-aid measures

General notes

Self-protection of the first aider.
Remove victim out of the danger area.
Take off immediately all contaminated clothing.
In all cases of doubt, or when symptoms persist, seek medical advice.

Following inhalation

Provide fresh air.

Solar Flux® Type B

Version number: 4.0

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions.

Following skin contact

After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water and soap.

Following eye contact

Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

Following ingestion

Rinse mouth. Do not induce vomiting.

Call a physician in any case.

Notes for the doctor

None.

4.2 Most important symptoms and effects, both acute and delayed

Varying degrees of pulmonary injury.

4.3 Indication of any immediate medical attention and special treatment needed

None.

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media

dry sand, use metal fire powder to extinguish

Unsuitable extinguishing media

water

5.2 Special hazards arising from the substance or mixture

Hazardous decomposition products: Section 10.

Hazardous combustion products

metal oxide smoke, toxic

5.3 Advice for firefighters

Non-combustible.

Keep containers cool with water spray.

In case of fire and/or explosion do not breathe fumes.

Coordinate firefighting measures to the fire surroundings.

Do not allow firefighting water to enter drains or water courses.

Collect contaminated firefighting water separately.

Fight fire with normal precautions from a reasonable distance.

Special protective equipment for firefighters

chemical protection suit, self-contained breathing apparatus (EN 133)

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Solar Flux® Type B

Version number: 4.0

For non-emergency personnel

Follow emergency procedures such as the need to evacuate the danger area or to consult an expert.

Remove persons to safety.

Ventilate affected area.

Avoid contact with skin and eyes.

Do not breathe dust.

Control of dust.

Wearing of suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

Warning and evacuating people in the neighborhood.

6.2 Environmental precautions

Knock down dust with water spray.

Keep away from drains, surface and ground water.

Retain contaminated washing water and dispose of it.

If substance has entered a water course or sewer, inform the responsible authority.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains.

Take up mechanically.

Advice on how to clean up a spill

Take up mechanically.

Collect spillage.

Other information relating to spills and releases

Place in appropriate containers for disposal.

Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5.

Personal protective equipment: see section 8.

Incompatible materials: see section 10.

Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Avoid contact with skin and eyes.

Do not breathe dust.

Obtain special instructions before use.

Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation.

Removal of dust deposits.

Solar Flux® Type B

Version number: 4.0

Specific notes/details

Dust deposits may accumulate on all deposition surfaces in a technical room.

Handling of incompatible substances or mixtures

Do not mix with acids.

Do not mix with alkali.

Do not mix with oxidizer

Measures to protect the environment

Avoid release to the environment.

Do not empty into drains; dispose of this material and its container at hazardous or special waste collection point.

Advice on general occupational hygiene

Do not eat, drink and smoke in work areas.

Wash hands after use.

Preventive skin protection (barrier creams/ointments) is recommended.

Remove contaminated clothing and protective equipment before entering eating areas.

Avoid contact with skin and eyes.

Do not breathe dust.

7.2 Conditions for safe storage, including any incompatibilities

Flammability hazards

None.

Incompatible substances or mixtures

Incompatible materials: see section 10.

Protect against external exposure, such as

heat

Consideration of other advice

Keep away from food, drink and animal feedingstuffs.

Ventilation requirements

Provision of sufficient ventilation.

Specific designs for storage rooms or vessels

Store locked up.

Keep container tightly closed and in a well-ventilated place.

Packaging compatibilities

Keep only in original container.

7.3 Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

The following constituents are the only constituents of the product which have a PEL, a TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

Solar Flux® Type B

Version number: 4.0

Occupational exposure limit values (Workplace Exposure Limits)									
Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m³]	STEL [ppm]	STEL [mg/m³]	Notation	Source
US	fluorides	-	PEL (CA)	-	2.5	-	-	F	Cal/OSHA PEL
US	fluorides	-	TLV®	-	2.5	-	-	F	ACGIH® 2025
US	fluorides	-	PEL	-	2.5	-	-	F	29 CFR 1910.1000
US	inorganic, solid fluorides	-	REL	-	2.5 (10 h)	-	-	F	NIOSH REL
US	Particulates not otherwise regulated	-	PEL (CA)	-	10	-	-	dust	Cal/OSHA PEL
US	Particulates not otherwise regulated	-	PEL (CA)	-	5	-	-	r	Cal/OSHA PEL
US	particulates not otherwise classified (PNOC)	-	PEL	-	15	-	-	dust	29 CFR 1910.1000
US	particulates not otherwise classified (PNOC)	-	PEL	1,765	-	-	-	partml, dust	29 CFR 1910.1000
US	particulates not otherwise classified (PNOC)	-	PEL	529.5	-	-	-	partml, r, dust	29 CFR 1910.1000
US	particulates not otherwise classified (PNOC)	-	PEL	-	5	-	-	r	29 CFR 1910.1000
US	particulate not otherwise regulated	-	REL	-	-	-	-	appx-D	NIOSH REL
US	boric acid	10043-35-3	TLV®	-	2	-	6	i	ACGIH® 2025
US	manganese, inorganic compounds	1313-13-9	TLV®	-	0.1	-	-	i, Mn	ACGIH® 2025
US	manganese, inorganic compounds	1313-13-9	TLV®	-	0.02	-	-	r, Mn	ACGIH® 2025
US	manganese compounds	1313-13-9	PEL (CA)	-	0.2	-	-	Mn	Cal/OSHA PEL
US	manganese compounds	1313-13-9	REL	-	1 (10 h)	-	3	Mn	NIOSH REL
US	manganese com-	1313-13-	PEL	-	-	-	-	Mn	29 CFR

Solar Flux® Type B

Version number: 4.0

Occupational exposure limit values (Workplace Exposure Limits)									
Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m³]	STEL [ppm]	STEL [mg/m³]	Notation	Source
	pounds	9							1910.1000
US	Calcium silicate, naturally occurring as Wollastonite	13983-17-0	TLV®	-	1	-	-	i, noAsb_less1Sil	ACGIH® 2025
US	quartz	14808-60-7	PEL (CA)	-	0.05	-	-	r, dust	Cal/OSHA PEL
US	silica, crystalline - quartz	14808-60-7	PEL	-	0.098	-	-	eq1a, r, dust	29 CFR 1910.1000
US	silica, crystalline - quartz	14808-60-7	PEL	-	0.294	-	-	eq2a, dust	29 CFR 1910.1000
US	silica, crystalline - quartz	14808-60-7	PEL	84.05	-	-	-	eq-ph1a, partml, r, dust	29 CFR 1910.1000
US	silica, crystalline - quartz	14808-60-7	TLV®	-	0.025	-	-	r	ACGIH® 2025
US	silica, crystalline - quartz	14808-60-7	PEL	-	0.05	-	-	r, dust	29 CFR 1910.1000
US	silica, crystalline - quartz	14808-60-7	REL	-	0.05 (10 h)	-	-	r, dust, appx-A	NIOSH REL
US	manganese	7439-96-5	PEL (CA)	-	0.2	-	-	-	Cal/OSHA PEL
US	manganese	7439-96-5	PEL (CA)	-	0.2	-	3	fume	Cal/OSHA PEL
US	manganese	7439-96-5	REL	-	1 (10 h)	-	3	fume	NIOSH REL
US	manganese	7439-96-5	PEL	-	-	-	-	fume	29 CFR 1910.1000
US	manganese	7439-96-5	TLV®	-	0.1	-	-	i	ACGIH® 2025
US	manganese	7439-96-5	TLV®	-	0.02	-	-	r	ACGIH® 2025

Notation

appx-A NIOSH Potential Occupational Carcinogen (Appendix A)

appx-D see Appendix D - Substances with No Established RELs

dust as dust

eq-ph1a $mppcf = 250/(\%SiO_2 + 5)$

eq1a $mg/m^3 = 10/(\%SiO_2 + 2)$

eq2a $mg/m^3 = 30/(\%SiO_2 + 2)$

Solar Flux® Type B

Version number: 4.0

Notation

F	calculated as F (fluorine)
fume	as fume
i	inhalable fraction
Mn	calculated as Mn (manganese)
noAsb_less	contains no asbestos and less than 1% free crystalline silica
1Sil	
partml	particles/ml
r	respirable fraction
STEL	short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)
TWA	time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

8.2 Exposure controls

Avoid contact during pregnancy/while nursing.

Appropriate engineering controls

Use local and general ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.

Hand protection

Protective gloves		
Material	Material thickness	Breakthrough times of the glove material
no information available	no information available	no information available

Wear suitable gloves.

Chemical protection gloves are suitable, which are tested according to EN 374.

Check leak-tightness/impermeability prior to use.

In the case of wanting to use the gloves again, clean them before taking off and air them well.

Body protection

Protective clothing for use against solid particulates.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Particle filter device (DIN EN 143).

Environmental exposure controls

Use appropriate container to avoid environmental contamination.

Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Solar Flux® Type B

Version number: 4.0

Appearance

Physical state	solid (powder)
Color	dark grey
Odor	odorless
Odor threshold	not determined

Other safety parameters

pH (value)	not applicable
Melting point/freezing point	not determined
Boiling point or initial boiling point and boiling range	1,682 °C
Flash point	not applicable
Evaporation rate	not determined
Flammability (solid, gas)	non-combustible
Explosive limits	not determined
Explosion limits of dust clouds	not determined
Vapor pressure	not determined
Density and/or relative density	
Density	2.2 g/cm³ at 20 °C
Relative vapour density	not relevant (solid)
Solubility(ies)	
Water solubility	42 mg/l not miscible in any proportion
Partition coefficient	
n-octanol/water (log KOW)	not relevant (inorganic)
Auto-ignition temperature	not determined
Decomposition temperature	not relevant
Viscosity	not relevant (solid)
Explosive properties	none
Oxidizing properties	none
Information for relevant hazard classes	hazard classes acc. to GHS (physical hazards):

Solar Flux® Type B

Version number: 4.0

according to GHS not relevant

9.2 Other information there is no additional information

SECTION 10: Stability and reactivity

10.1 Reactivity

No information available.

10.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

See below "Conditions to avoid".

10.3 Possibility of hazardous reactions

Contact with acids liberates very toxic gas.

10.4 Conditions to avoid

Control of dust.

10.5 Incompatible materials

acids, bases, oxidizers, aluminum, halogen

10.6 Hazardous decomposition products

Hazardous combustion products: see section 5.

Hydrogen fluoride (HF).

Metallic oxides containing heavy metals.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Classification procedure

If not otherwise specified the classification is based on:

Ingredients of the mixture (additivity formula).

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Acute toxicity

Test data are not available for the complete mixture.

Acute toxicity of components

Name of substance	CAS No	Exposure route	End-point	Value	Species	Method	Source
calcium fluoride	7789-75-5	inhalation: dust/mist	LC50	>5,070 mg/m ³ /4h	rat	OECD Guideline 403	ECHA
calcium fluoride	7789-75-5	oral	LD0	>2,000	rat, fe-	OECD	ECHA

Solar Flux® Type B

Version number: 4.0

Acute toxicity of components							
Name of substance	CAS No	Expos-ure route	End-point	Value	Species	Method	Source
				mg/kg	male	Guideline 423	
boric acid	10043-35-3	oral	LD50	3,450 mg/kg	rat, male	-	ECHA
boric acid	10043-35-3	oral	LD50	4,080 mg/kg	rat, female	-	ECHA
boric acid	10043-35-3	dermal	LD0	>2,000 mg/kg	rabbit	FIFRA (40 CFR 163)	ECHA
manganese	7439-96-5	oral	LD0	>2,000 mg/kg	rat, female	OECD Guideline 420	ECHA
manganese	7439-96-5	inhala-tion: dust/mis-t	LC0	>5.14 mg/4h	rat	OECD Guideline 403	ECHA
lithium fluoride	7789-24-4	oral	LD50	706 mg/kg	rat	OECD Guideline 401	ECHA
lithium fluoride	7789-24-4	inhala-tion: dust/mis-t	LC50	>15.57 mg/4h	rat	OECD Guideline 403	ECHA
lithium fluoride	7789-24-4	dermal	LD50	>2,000 mg/kg	rat	OECD Guideline 402	ECHA

Skin corrosion/irritation

Classification could not be established because:

Data are lacking, inconclusive, or conclusive but not sufficient for classification.

Serious eye damage/eye irritation

Classification could not be established because:

Data are lacking, inconclusive, or conclusive but not sufficient for classification.

Respiratory or skin sensitization

Skin sensitization

Classification could not be established because:

Data are lacking, inconclusive, or conclusive but not sufficient for classification.

Respiratory sensitization

Classification could not be established because:

Data are lacking, inconclusive, or conclusive but not sufficient for classification.

Germ cell mutagenicity

Solar Flux® Type B

Version number: 4.0

Classification could not be established because:

Data are lacking, inconclusive, or conclusive but not sufficient for classification.

Carcinogenicity

May cause cancer.

IARC Monographs

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans			
Name of substance	CAS No	Classification	Number
Solar Flux® Type B		1	-
quartz	14808-60-7	1	-
lithium fluoride		3	-
wollastonite (calcium metasilicate)	13983-17-0	3	-
calcium fluoride		3	-

Legend

1 Carcinogenic to humans
3 Not classifiable as to carcinogenicity in humans

National Toxicology Program (United States)

None of the ingredients are listed.

OSHA Carcinogens

None of the ingredients are listed.

Reproductive toxicity

May damage the unborn child (if swallowed).

May damage fertility (if swallowed).

Specific target organ toxicity - single exposure

Classification could not be established because:

Data are lacking, inconclusive, or conclusive but not sufficient for classification.

Specific target organ toxicity - repeated exposure

Classification could not be established because:

Data are lacking, inconclusive, or conclusive but not sufficient for classification.

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

11.2 Other information

There is no additional information.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity (acute)

Based on available data, the classification criteria are not met.

Solar Flux® Type B

Version number: 4.0

Aquatic toxicity (acute) of components

Name of substance	CAS No	Endpoint	Exposure time	Value	Species	Method	Source
manganese	7439-96-5	LC50	96 h	>3.6 mg/l	rainbow trout (Oncorhynchus mykiss)	OECD Guideline 203	ECHA Chem
manganese	7439-96-5	EC50	48 h	>1.6 mg/l	daphnia magna	OECD Guideline 202	ECHA Chem
manganese	7439-96-5	EC50	72 h	2.8 mg/l	green algae (Desmodesmus subspicatus)	OECD Guideline 201	ECHA Chem
manganese	7439-96-5	ErC50	72 h	4.5 mg/l	green algae (Desmodesmus subspicatus)	OECD Guideline 201	ECHA
lithium fluoride	7789-24-4	EC50	48 h	132.4 mg/l	aquatic invertebrates	-	ECHA
lithium fluoride	7789-24-4	EC50	72 h	112 mg/l	algae (Desmodesmus subspicatus)	OECD Guideline 201	ECHA
lithium fluoride	7789-24-4	ErC50	72 h	>400 mg/l	algae (Desmodesmus subspicatus)	OECD Guideline 201	ECHA

Aquatic toxicity (chronic)

Based on available data, the classification criteria are not met.

Aquatic toxicity (chronic) of components

Name of substance	CAS No	Endpoint	Exposure time	Value	Species	Method	Source
calcium fluoride	7789-75-5	NOEC	20 h	14.6 mg/l	microorganisms	-	ECHA
calcium fluoride	7789-75-5	NOEC	28 h	464 mg/l	microorganisms	-	ECHA
calcium fluoride	7789-75-5	NOEC	16 h	474.5 mg/l	microorganisms	-	ECHA
calcium fluoride	7789-75-5	NOEC	3 h	510 mg/l	microorganisms	-	ECHA
manganese dioxide	1313-13-9	EC50	3 h	>1,000 mg/l	Bacteria (activated sludge)	OECD Guideline 209	ECHA
manganese dioxide	1313-13-9	NOEC	3 h	1,000 mg/l	Bacteria (activated sludge)	OECD Guideline 209	ECHA

Solar Flux® Type B

Version number: 4.0

Name of substance	CAS No	Endpoint	Exposure time	Value	Species	Method	Source
manganese	7439-96-5	EC50	3 h	1,000 mg/l	activated sludge of a predominantly domestic sewage	OECD Guideline 209	ECHA
manganese	7439-96-5	NOEC	8 d	1.7 mg/l	water flea (Daphnia)	OECD Guideline 211	ECHA Chem
manganese	7439-96-5	NOEC	72 h	2.5 mg/l	green algae (Desmodesmus subspicatus)	OECD Guideline 201	ECHA
manganese	7439-96-5	NOEC	3 h	1,000 mg/l	activated sludge of a predominantly domestic sewage	OECD Guideline 209	ECHA
manganese	7439-96-5	LOEC	72 h	5.3 mg/l	green algae (Desmodesmus subspicatus)	OECD Guideline 201	ECHA
manganese	7439-96-5	growth (Eb-Cx) 10%	72 h	2.6 mg/l	green algae (Desmodesmus subspicatus)	OECD Guideline 201	ECHA
manganese	7439-96-5	growth (Eb-Cx) 20%	72 h	2.6 mg/l	green algae (Desmodesmus subspicatus)	OECD Guideline 201	ECHA
manganese	7439-96-5	growth rate (ErCx) 10%	72 h	3.4 mg/l	green algae (Desmodesmus subspicatus)	OECD Guideline 201	ECHA
manganese	7439-96-5	growth rate (ErCx) 20%	72 h	3.7 mg/l	green algae (Desmodesmus subspicatus)	OECD Guideline 201	ECHA
lithium fluoride	7789-24-4	NOEC	21 d	14.1 mg/l	daphnia magna	-	ECHA
lithium fluoride	7789-24-4	NOEC	21 d	4 mg/l	rainbow trout (Oncorhynchus mykiss)	-	ECHA
lithium fluoride	7789-24-4	NOEC	72 h	25 mg/l	algae (Desmodesmus subspicatus)	OECD Guideline 201	ECHA
lithium fluoride	7789-24-4	LOEC	72 h	50 mg/l	algae (Desmodesmus subspicatus)	OECD Guideline 201	ECHA
lithium fluoride	7789-24-4	growth rate (ErCx) 10%	72 h	80 mg/l	algae (Desmodesmus subspicatus)	OECD Guideline 201	ECHA

12.2 Persistence and degradability

Solar Flux® Type B

Version number: 4.0

Biodegradation

No data available.

Persistence

No data available.

12.3 Bioaccumulative potential

n-octanol/water (log KOW) not relevant
(inorganic)

Bioaccumulative potential of components

Name of substance	CAS No	BCF	Log KOW
calcium fluoride	7789-75-5	≤0.66	-
boric acid	10043-35-3	-	-1.09 (pH value: 7.5, 22 °C)
manganese	7439-96-5	19	-

12.4 Mobility in soil

No data available.

12.5 Results of PBT and vPvB assessment

Does not contain a PBT-/vPvB-substance at a concentration of $\geq 0.1\%$.

12.6 Other adverse effects

Data are not available.

Remarks

Keep away from drains, surface and ground water.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Dispose of contents/container in accordance with local/regional/national/international regulations.

Sewage disposal-relevant information

Do not empty into drains.

Waste treatment of containers/packages

Completely emptied packages can be recycled.

Handle contaminated packages in the same way as the substance itself.

Remarks

Please consider the relevant national or regional provisions.

SECTION 14: Transport information

14.1 UN number not subject to transport regulations

14.2 UN proper shipping name -

14.3 Transport hazard class(es) -

Solar Flux® Type B

Version number: 4.0

14.4 Packing group -

14.5 Environmental hazards -

14.6 Special precautions for user -

14.7 Transport in bulk according to IMO instruments -

14.8 Information for each of the UN Model Regulations

Transport of dangerous goods by road or rail (49 CFR US DOT) Additional information

Not subject to transport regulations.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations specific for the product in question

National regulations (United States)

Toxic Substance Control Act (TSCA) Not all ingredients are listed (ACTIVE)

Superfund Amendment and Reauthorization Act (SARA TITLE III)

The List of Extremely Hazardous Substances and Their Threshold Planning Quantities (EPCRA Section 302, 304)

None of the ingredients are listed

Specific Toxic Chemical Listings (EPCRA Section 313)

Toxics Release Inventory: Specific Toxic Chemical Listings				
Name of substance	Name acc. to inventory	CAS No	Remarks	Effective date
manganese dioxide	manganese compounds		-	1987-01-01
aluminium oxide	aluminium oxide	1344-28-1	fibrous forms	1987-01-01
aluminium powder (pyrophoric)	aluminium	7429-90-5	fume or dust	1987-01-01
manganese	manganese	7439-96-5	-	1987-01-01

Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA)

List of Hazardous Substances and Reportable Quantities (CERCLA section 102a) (40 CFR 302.4)

None of the ingredients are listed

Clean Air Act

None of the ingredients are listed

Right to Know Hazardous Substance List

Solar Flux® Type B

Version number: 4.0

Toxic or Hazardous Substance List (MA-TURA)

Name of substance	Name acc. to inventory	CAS No	DEP CODE	PBT / HHS / LHS	PBT / HHS Threshold	De Minimis Concentration Threshold
quartz	Silica, crystalline (respirable, < 10 microns) in abrasive blasting or molding	-	1095	-	-	1.0 %
quartz	Silica, crystalline (respirable, < 10 microns) in abrasive blasting or molding	-	1095	-	-	1.0 %
manganese dioxide	Manganese Compounds	-	1027	-	-	1.0 %
aluminium oxide	Aluminum oxide (fibrous forms)	1344-28-1	-	-	-	1.0 %
aluminium powder (pyrophoric)	Aluminum (fume or dust)	7429-90-5	-	-	-	1.0 %
manganese	Manganese	7439-96-5	-	-	-	1.0 %
manganese	Manganese Compounds	-	1027	-	-	1.0 %

Hazardous Substances List (MN-ERTK)

Name of substance	Name acc. to inventory	CAS No	References	Remarks
quartz	Silica - Crystalline	-	A, *	-
Rutil Titandioxid - NICHT verwenden! Besser CSB 018358 - Siehe Handbuch!	Dust, Inert or Nuisance (When toxic impurities are not present, for example, quartz less than 1 percent.)	-	A	dust
lithium fluoride	Fluoride, as F	16984-48-8	A, N, O	dust
lithium fluoride	Fluorides, inorganic	-	N	-
manganese dioxide	Manganese, elemental and compounds, as Mn	-	A, O	-
wollastonite (calcium metasilicate)	Dust, Inert or Nuisance (When toxic impurities are not present, for example, quartz less than 1 percent.)	-	A	dust
manganese	Manganese, elemental and compounds, as Mn	-	A, O	-
calcium fluoride	Fluoride, as F	16984-48-8	A, N, O	dust
calcium fluoride	Fluorides, inorganic	-	N	-

Legend

* Substances which are regulated by OSHA as carcinogens; have been categorized by the ACGIH as either "human

Solar Flux® Type B

Version number: 4.0

Legend

carcinogens" or "suspect of carcinogenic potential for man"; have been evaluated by the International Agency for Research on Cancer (IARC) and found to be carcinogens or potential carcinogens; or have been listed as a carcinogen or potential carcinogen in the Annual Report on Carcinogens published by the National Toxicology Program (NTP).

A American Conference of Governmental Industrial Hygienists (ACGIH), "Threshold Limit Values for Chemical Substances and Physical Agents and Biological Exposure Indices for 1992-93", available from ACGIH

dust If the substance poses an airborne particulate exposure hazard, the substance is followed by the word "dust."

N National Institute for Occupational Safety and Health (NIOSH), "Recommendations for Occupational Safety and Health Standards," August 1988, available from NIOSH, Publications Dissemination Office, Division of Standards Development and Technology Transfer

O Occupational Safety and Health Administration (OSHA), Safety and Health Standards, Code of Federal Regulations, title 29, part 1910, subpart Z, "Toxic and Hazardous Substances, 1990." General information: Minnesota Department of Labor and Industry, Occupational Safety and Health Division

Hazardous Substance List (NJ-RTK)

Name of substance	Name acc. to inventory	CAS No	Remarks	Classifications	Listed in	Substance number	DOT number
quartz	SILICA, QUARTZ (QUARTZ (SiO ₂), SILICA, CRYSTALLINE-QUARTZ)	14808-60-7	-	CA.	1 2 4 5 7	1660	-
calcium carbonate	calcium carbonate (limestone)	1317-65-3	-		1 4	4001	-
lithium fluoride	fluorides	-	-		1 2 4	0936	-
quartz	SILICA, QUARTZ (QUARTZ (SiO ₂), SILICA, CRYSTALLINE-QUARTZ)	14808-60-7	-	CA.	1 2 4 5 7	1660	-
Ferrosilicon	ferrosilicon	8049-17-0	-	F2 R2.	3 17	0927	1408
titanium dioxide	titanium dioxide	13463-67-7	-		1 2 4 7	1861	-
manganese dioxide	manganese compounds	-	-		1 2 4 6 18 20	2324	-
aluminium oxide	ALUMINUM OXIDE	1344-	-		1	2891	-

Solar Flux® Type B

Version number: 4.0

Name of substance	Name acc. to inventory	CAS No	Remarks	Classifications	Listed in	Substance number	DOT number
	(ALUMINUM OXIDE (Al ₂ O ₃), alpha-ALUMINA)	28-1			2 4 6 18		
aluminium powder (pyrophoric)	ALUMINUM	7429-90-5	-	F3 R1.	1 2 3 4 6 15 17 18	0054	1396
manganese	manganese	7439-96-5	-	F3 R1.	1 2 3 4 6 8 17 18 20	1155	3089
silicon	silicon	7440-21-3	-	F3.	1 3 4 17	3125	1346
titanium	titanium	7440-32-6	-	F3 R1.	3 17	1860	2546
carbon	graphite	7782-42-5	-		1 2 4	3325	-
calcium fluoride	fluorides	-	-		1 2 4	0936	-

Legend

- 1 Occupational Safety and Health Administration, 29 CFR 1910-Occupational Safety and Health Standards, Subpart Z-Toxic and Hazardous Substances, July 1, 2008.
- 15 "Fire Protection Guide to Hazardous Materials," NFPA 49 (Hazardous Chemicals Data), NFPA 325 (Guide to Fire Hazard Properties of Flammable Liquids, Gases, and Volatile Solids), and NFPA 704 (Standard System for the Identification of the Hazards of Materials for Emergency Response), National Fire Protection Association (NFPA), 2001.
- 17 "2008 Emergency Response Guidebook," Research and Special Programs Administration, U.S. Department of Transportation, 2008.
- 18 List of Toxics Release Inventory Chemicals, Section 313, Emergency Planning and Community Right to Know Act (EPCRA), Toxics Release Inventory (TRI) Program, U.S. Environmental Protection Agency, 40 CFR 372.65, July 1, 2008.

Solar Flux® Type B

Version number: 4.0

Legend

2 "2009 TLVs® and BEIs®, Threshold Limit Values and Biological Exposure Indices," American Conference of Governmental Industrial Hygienists (ACGIH), 2009.

20 List of Hazardous Substances and Reportable Quantities (RQ) , Comprehensive Environmental Response, Compensation and Liability Act of 1980 (CERCLA), U.S. Environmental Protection Agency, 40 CFR 302, Table 302.4, July 1, 2008.

3 Office of Hazardous Materials Safety, Research and Special Programs Administration, U.S. Department of Transportation, 49 CFR 172.101-Hazardous Materials Table, October 1, 2008.

4 "NIOSH Pocket Guide to Chemical Hazards," National Institute for Occupational Safety and Health (NIOSH), U.S. Department of Health and Human Services, No. 2005-149, September 2005.

5 "Eleventh Report on Carcinogens, 2004," National Toxicology Program, National Institute of Environmental Health Sciences, Public Health Service, U.S. Department of Health and Human Services, 2004.

6 "Environmental Hazardous Substance List," New Jersey Department of Environmental Protection, N.J.A.C. 7:1G-2, as printed in the Community Right to Know Survey Instruction Book, 2008.

7 IARC Monographs on the Evaluation of Carcinogenic Risks to Humans, "All Supplements, All Volumes, Groups 1, 2A, 2B, and 3, International Agency for Research on Cancer (IARC), World Health Organization, 2008.

8 Integrated Risk Information System (IRIS) Database for Risk Assessment, Office of Research and Development, National Center for Environmental Assessment, U.S. Environmental Protection Agency (EPA), September 2008.

CA Carcinogenic

F2 Flammable - Second Degree

F3 Flammable - Third Degree

R1 Reactive - First Degree

R2 Reactive - Second Degree

Hazardous Substance List (Chapter 323) (PA-RTK)

Name acc. to inventory	CAS No	Classification
QUARTZ (SIO ₂)	14808-60-7	-
RUTILE (TIO ₂)	1317-80-2	-
MANGANESE	7439-96-5	*, E
ALUMINUM OXIDE (AL ₂ O ₃)	1344-28-1	E
ALUMINUM	7429-90-5	E
ALUMINUM PRODUCTION	-	S
MANGANESE	7439-96-5	*, E

Legend

* Any compound of this substance is also an environmental hazard

E Environmental hazard

S Special hazardous substance

Hazardous Substance List (RI-RTK)

Name of substance	Name acc. to inventory	CAS No	References
quartz	Fibrous glass dust	14808-60-7	T
quartz	Glass (fibrous or dust)	14808-60-	T

Solar Flux® Type B

Version number: 4.0

Name of substance	Name acc. to inventory	CAS No	References
		7	
calcium carbonate	Calcium carbonate/Marble	1317-65-3	T
calcium carbonate	Limestone	1317-65-3	T
calcium carbonate	Marble	1317-65-3	T
quartz	Fibrous glass dust	14808-60-7	T
quartz	Glass (fibrous or dust)	14808-60-7	T
titanium dioxide	Titanium dioxide	13463-67-7	T
aluminium oxide	Aluminum oxide - "inert" particulate	1344-28-1	T
aluminium oxide	alpha-Alumina	1344-28-1	T
aluminium powder (pyrophoric)	Aluminum (Dust or Powder), metal & oxide, welding fumes	7429-90-5	T, F
manganese	Manganese, as Mn.	7439-96-5	T
silicon	Silicon	7440-21-3	T
carbon	Graphite (synthetic)	7440-44-0	T

Legend

F Flammability (NFPA®)

T Toxicity (ACGIH®)

California Environmental Protection Agency (Cal/EPA): Proposition 65 - Safe Drinking Water and Toxic Enforcement Act of 1987

Proposition 65 List of chemicals			
Name acc. to inventory	CAS No	Remarks	Type of the toxicity
silica, crystalline	-	airborne particles of respirable size	cancer
silica, crystalline	-	airborne particles of respirable size	cancer
titanium dioxide	13463-67-7	airborne, unbound particles of respirable size	cancer

Drug precursors, Chemicals designated within the Controlled Substances Act, 21 U.S.C. § 802, paragraphs 34 (list I) and 35 (list II)

None of the ingredients are listed

SECTION 16: Other information, including date of preparation or last revision

Date of preparation: 2021-02-16

Solar Flux® Type B

Version number: 4.0

Date of last revision: 2025-11-05.

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
29 CFR 1910.1000	29 CFR 1910.1000, Tables Z-1, Z-2, Z-3 - Occupational Safety and Health Standards: Toxic and Hazardous Substances (permissible exposure limits)
49 CFR US DOT	49 CFR U.S. Department of Transportation
ACGIH®	American Conference of Governmental Industrial Hygienists
ACGIH® 2025	From ACGIH®, 2025 TLVs® and BEIs® Book. Copyright 2025. Reprinted with permission. Information on the proper use of the TLVs® and BEIs®: http://www.acgih.org/tlv-bei-guidelines/policies-procedures-presentations/tlv-bei-position-statement
Acute Tox.	Acute toxicity
BCF	Bioconcentration factor
Cal/OSHA PEL	California Division of Occupational Safety and Health (Cal/OSHA): Permissible Exposure Limits (PELs)
Carc.	Carcinogenicity
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
cD	Combustible dust
DEP CODE	Department of Environmental Protection Code
DGR	Dangerous Goods Regulations (see IATA/DGR)
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
ErC50	≡ EC50: in this method, that concentration of test substance which results in a 50 % reduction in either growth (EBC50) or growth rate (ErC50) relative to the control
Eye Dam.	Seriously damaging to the eye
Eye Irrit.	Irritant to the eye
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
HHS	Higher hazard substance
IARC	International Agency for Research on Cancer
IARC Monographs	IARC Monographs on the Evaluation of Carcinogenic Risks to Humans
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
IMDG	International Maritime Dangerous Goods Code
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
LD50	Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval
LHS	Lower hazard substance

Solar Flux® Type B

Version number: 4.0

Abbr.	Descriptions of used abbreviations
LOEC	Lowest Observed Effect Concentration
log KOW	n-Octanol/water
NFPA®	National Fire Protection Association (United States)
NIOSH REL	National Institute for Occupational Safety and Health (NIOSH): Recommended Exposure Limits (RELS)
NOEC	No Observed Effect Concentration
OSHA	Occupational Safety and Health Administration (United States)
PBT	Persistent, Bioaccumulative and Toxic
PEL	Permissible exposure limit
ppm	Parts per million
Repr.	Reproductive toxicity
RTECS	Registry of Toxic Effects of Chemical Substances (database of NIOSH with toxicological information)
STEL	Short-term exposure limit
STOT RE	Specific target organ toxicity - repeated exposure
TLV®	Threshold Limit Values
TWA	Time-weighted average
vPvB	Very Persistent and very Bioaccumulative

Key literature references and sources for data

OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200 (May 20, 2024 eff. July 19, 2024).

Transport of dangerous goods by road or rail (49 CFR US DOT).

International Maritime Dangerous Goods Code (IMDG).

Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties.

Health hazards.

Environmental hazards.

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H302	Harmful if swallowed.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H350	May cause cancer.
H360FD	May damage fertility. May damage the unborn child (if swallowed).
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.

Solar Flux® Type B

Version number: 4.0

Code	Text
OSHA003	May form combustible dust concentrations in air.

Responsible for the safety data sheet

Chemical Regulatory Compliance Company
Jasper, GA
USA

Telephone: +1 (630) 410-1660

e-Mail: GHS@crc-us.com

Website: www.crc-us.com

Disclaimer

This information is based upon the present state of our knowledge.
This SDS has been compiled and is solely intended for this product.